The role of electric vehicles in near-term mitigation pathways and achieving the UK's carbon budget

Graeme Hill^{a,*}, Oliver Heidrich^b, Felix Creutzig^{c,d}, Phil Blythe^a

^a School of Engineering, Systems for Future Mobility, Newcastle University, Newcastle upon Tyne NE1 7RU, UK

^b School of Engineering, Tyndall Centre for Climate Change Research, Newcastle University, Newcastle upon Tyne NE1 7RU, UK

^c Mercator Research Institute on Global Commons and Climate Change, Torgauer Str. 12-15, 10829 Berlin, Germany

^d Sustainability Economics of Human Settlements, Technical University Berlin, Straße des 17. Juni 135, 10623 Berlin, Germany

HIGHLIGHTS

- An accelerated EV program is needed to meet 2050 CO₂ emission targets for the UK.
- Even under accelerated uptake, few CO₂ benefits will be seen before 2030.
- The lack of impact before 2030 derives from slow vehicle stock turnover.
- With embedded production CO₂, 2050 UK targets will need intense grid decarbonisation.
- There is an urgent need to pursue both EV uptake and demand side solutions.

ARTICLE INFO

Keywords:

Electric vehicles
Vehicle ownership
Vehicle production
Stock flow model
Climate change mitigation

ABSTRACT

The decarbonisation of the road transport sector is increasingly seen as a necessary component to meet global and national targets as specified in the Paris Agreement. It may be achieved best by shifting from Internal Combustion Engine (ICE) cars to Electric Vehicles (EVs). However, the transition to a low carbon mode of transport will not be instantaneous and any policy or technological change implemented now will take years to have the desired effect. Within this paper we show how on-road emission factors of EVs and models of embedded CO₂ in the vehicle production may be combined with statistics for vehicle uptake/replacement to forecast future transport emissions. We demonstrate that EVs, when compared to an efficient ICE, provide few benefits in terms of CO₂ mitigation until 2030. However, between 2030 and 2050, predicted CO₂ savings under the different EV uptake and decarbonisation scenarios begin to diverge with larger CO₂ savings seen for the accelerated EV uptake. This work shows that simply focusing on on-road emissions is insufficient to model the future CO₂ impact of transport. Instead a more complete production calculation must be combined with an EV uptake model. Using this extended model, our scenarios show how the lack of difference between a Business as Usual and accelerated EV uptake scenario can be explained by the time-lag in cause and effect between policy changes and the desired change in the vehicle fleet. Our work reveals that current UK policy is unlikely to achieve the desired reduction in transport-based CO₂ by 2030. If embedded CO₂ is included as part of the transport emissions sector, then all possible UK EV scenarios will miss the reduction target for 2050 unless this is combined with intense decarbonisation (80% of 1990 levels) of the UK electricity grid. This result highlights that whilst EVs offer an important contribution to decarbonisation in the transport sector it will be necessary to look at other transport mitigation strategies, such as modal shift to public transit, car sharing and demand management, to achieve both near-term and long-term mitigation targets.

1. Introduction

The transport sector has been identified as a key barrier to decarbonisation based on the high costs of substituting energy-dense liquid

fossil fuels [1,2]. A potential solution is in the transition to electromobility, and more specifically a shift from gasoline and diesel cars to electric vehicles (EVs). Previous research has demonstrated that EVs offer the potential for large scale reduction in carbon dioxide (CO₂)

* Corresponding author.

E-mail addresses: g.a.hill@ncl.ac.uk (G. Hill), Oliver.Heidrich@ncl.ac.uk (O. Heidrich), Creutzig@mcc-berlin.net (F. Creutzig), phil.blythe@ncl.ac.uk (P. Blythe).

<https://doi.org/10.1016/j.apenergy.2019.04.107>

Received 31 July 2018; Received in revised form 21 March 2019; Accepted 16 April 2019

0306-2619/© 2019 The Authors. Published by Elsevier Ltd. This is an open access article under the CC BY license (<http://creativecommons.org/licenses/by/4.0/>).

emissions from the transport sector. The assertion that EVs can deliver high CO₂ emissions reductions requires better underpinning of detailed national or regional studies that are informed both by empirical and conceptual detail. The UK, which consists of four countries: England, Wales, Northern Ireland and Scotland covering an area of 243,610 km² and an estimated population of about 62 million people, offers itself as an attractive case study due to its generally progressive climate policies [3,4] and insular location, which reduces dependencies on international and transit road users. In 2008, the Climate Change Act 2008 [5] was introduced in the UK with the stated aim of reducing UK greenhouse gas (GHG) emissions to 80% of the 1990 levels by 2050. The Committee of Climate Change [6] estimated that transport is one of the largest CO₂ emitters in the UK, with emissions in 2016 amounting to 26% of the total GHG emissions. However, contrasting with substantial reductions in other sectors, the transport sector has stagnated with the total emitted CO₂ remaining approximately equivalent to 1990 levels, without any apparent signs of improvement. [7]

As road transport makes up 91% of domestic transport emissions with cars and taxis accounting for 56% of all transport CO₂ emissions in 2016 [8], one climate change mitigation strategy within the UK is to focus on a shift to EVs in the passenger car fleet. To facilitate this the UK Government has published the Policy Paper 'Clean Growth Strategy' [9], which has described the role EVs will play in both driving and decarbonising the UK economy, in addition to the 'Road to Zero' policy paper [10]. EV ownership increased by 180% in 2017 with 53,000 newly registered vehicles, or 1.7% of all newly registered vehicles [11]. Whilst this demonstrates a continued increase in EV purchase rates, it is clear a bigger shift is needed to achieve 2050 CO₂ emission reduction targets, with the Committee for Climate Change [12] estimating that by 2030 some 60% of all newly registered vehicles will need to be an EV.

The fundamental goal of this research is to examine whether the UK's EV adoption policy, coupled with the likely technological changes and vehicle transition models, will allow the UK to meet the transport CO₂ emission targets in both the near-term (2018–2030), and mid-term (2030–2050) timescales. This is achieved through investigating the climate mitigation effects of electrifying the UK's passenger automobile fleet, including emissions from both car usage and vehicle production and including the likely timescales for the transition to EVs from ICE vehicles.

Previous work has looked at the impact of EV adoption on reducing CO₂ emissions [13–15] and the impact on materials usage [16], including possible forthcoming shortages in the necessary materials for large scale EV adoption [17]. However this paper shows how embedded CO₂, which is defined in this paper as the CO₂ emitted during the production of vehicles, coupled with actual vehicle adoption data may be used to determine the overall impact of EV adoption on the CO₂ footprint of the transport sector within the UK. More specifically, we examine how the UK may, or may not, meet the transport emission targets for CO₂ reduction set out in the Climate Change Act 2008 [5] and how the inclusion of embedded CO₂ will affect the overall emission reduction.

We show that even with accelerated EV adoption ambitions, the volume of EVs and thus their impact on CO₂ emissions reduction, will remain comparatively low until at least 2030. However, we provide evidence that post 2030, under all EV adoption scenarios, the volume of EVs and their cumulative CO₂ emission reductions will begin to substantially increase. It will thus become necessary for cities, regions, and countries to implement a dedicated EV policy framework designed to facilitate the transition to a low CO₂ emission passenger transport fleet in the mid-term, but also to draw on other options, such as modal shift and incentivized telecommuting, to reach the UK's near-term CO₂ emission mitigation targets.

1.1. Transport sector GHG emissions

In 2016 the transport sector, including international aviation,

accounted for 1080 MtCO₂e (the total weight of CO₂ which would have an equivalent global warming potential) and contributed 27% to the total GHG emissions across EU-28 countries [18]. Notably, it is the only sector which has seen a rise of GHG emissions compared to 1990 levels. This increasing share of GHG emissions from the transport sector follows a structural change dynamic, where the shift of economies from industry to services corresponds to a rise of transport intensity in energy use [19,20]. It is however also rooted in a supply/demand game of making vehicles increasingly powerful and heavier thus compensating for gains in technological efficiency [21]. The EU has developed a range of policies in order to mitigate the effects from transport on climate change with the majority aimed at reducing CO₂ emissions, and hence reducing total GHG emissions:

- CO₂ emissions for new cars and vans: Car manufacturers have to ensure that their new car fleet does not emit more than an average of 130 g CO₂/km by 2015 and 95 g CO₂/km by 2020. Recent regulation proposals [22] have improved this to 67 gCO₂/km by 2030, a reduction of 30% over the 2020 levels.
- CO₂ labelling of cars: EU legislation ensures that consumers are informed about the fuel efficiency and CO₂ emissions for new cars.
- Fuel quality: EU legislation requires the GHG intensity of vehicle fuels to be cut by up to 10% by 2020.

Actions and inactions by central, regional, and local governments will have profound effects as cities across Europe introduce mitigation strategies to tackle the causes of climate change [3,23]. The European Parliament has committed its member states to an ambitious climate change strategy reducing GHG emissions and energy consumption by at least 20% by 2020 using a 1990 baseline [24].

Importantly, the EU points to cities and local authorities as key authorities to help the transition to low-carbon road transport. Local actions explicitly includes the promotion of active travel, mode shift to public transport, and schemes to reduce congestion. Cities can adopt a full spectrum of policies available to promote low-carbon road transport at local scale that involve procurement of electric vehicles, stringent parking management, and the expansion of comfortable and safe bike lanes. Importantly, many (but not all) of these policies can be implemented within short time scales, and have immediate impact on daily routines and travel choices. They may hence complement EU wide action and provide near-term starting points for reducing transport CO₂ emissions on the demand side.

1.2. EVs and national climate change mitigation targets

EVs have two major characteristics that render them key candidates as new car technology. First, they can be charged with electricity from low or non-CO₂ emitting sources, which enables deeper decarbonisation than for vehicles powered by biofuels [25].

Second, electric engines are vastly more efficient than ICEs or other proposed technologies, such as compressed-air cars [26].

A study of the US car industry showed that EVs were a relatively small market, lacking governmental guidance and policies with little motivation for car-makers to accelerate their strategies away from ICE technology [27]. However, a more recent review [28] has shown a strong causal link between EV incentives and EV uptake, indicating a growing market. In order to make road transport more sustainable, the UK Government has promoted the uptake of ultra-low carbon vehicles such as EVs, hydrogen powered vehicles, and vehicles powered by biofuels [29] and to promote economic growth and to cut CO₂ emissions across England [30].

Fig. 1. Comparison of Business as Usual and 2040 EV Adoption Target Scenarios, 2010–2040.

2. Research data and methodology

2.1. Calculating vehicle stock turnover and UK EV adoption rates

The UK Committee on Climate Change surface transport CO₂ abatement scenario from the fifth carbon budget [31] posits that EV sales should reach 60% of all new car sales by 2030, which would require a growth rate in annual purchases of 33%.

This, combined with the introduction of a ban on the sale of new petrol and diesel passenger cars and small vans in 2040 by the UK government in 2017 [32] has allowed the creation of a series of predictions on the expected EV adoption rate within the UK, which would be required to meet this target. By extrapolating to the 2040 target from existing EV sales rates, which show an increase of 2074 in 2011 up to 5300 in 2017 [11], it is possible to predict EV sales up to 2040. This prediction for EV car sales is shown in Fig. 1 along with a “Business as Usual” case which assumes that current trends in EV sales will dominate future rates [33].

To understand the impact of EV penetration, and the possible consequences of policies dealing with EV purchases, it is necessary to understand how EV penetration will affect the passenger vehicle population. The effective in-use CO₂ footprint of a vehicle fleet will be determined by the age of the fleet, the distribution of different vehicle fuel-types and the annual mileage for the combination of these two variables.

The UK Road Traffic Forecasts 2015 [34] predict that the expected number of cars in the UK will grow from 25 m in 2010 to approximately 35 m in 2040. Therefore, to determine the vehicle population it is necessary to apply the scrappage rate to the vehicle population and then allow a new vehicle purchase level which will match the predicted total car numbers. This may be described as:

$$\Delta V = P - SV \quad (1)$$

where V is the vehicle population, P is the purchase rate and S is the scrappage rate. The vehicle population can be expanded into a more complete form.

$$V^y = \sum_{a=age} V_a^y \quad (2)$$

where V^y is the total number of vehicles in year y and V_a^y is the number of vehicles in year y of age a .

$$V^{y+1} = \alpha P^{y+1} + \sum_a V_a^y (1 - \beta S_a) \quad (3)$$

Combining (1) and (2) gives (3) where P^{y+1} is the purchase rate in year $y + 1$, S_a is the scrappage rate for a vehicle of age a . α and β are “balancing” variables to allow the change in vehicle numbers to match our predicted numbers.

The scrappage rate is derived from a road worthiness test, the UK Ministry of Transport test, conducted annually for each vehicle in the UK. The data is collated and released in an anonymised form by the UK

Department for Transport [35]. Contained within the dataset is the result of each road worthiness test, including a unique vehicle ID which allows vehicles to be tracked in subsequent years and only disappears from the dataset when that vehicle is scrapped or otherwise taken off-road. Previous work [36] has used this data to explore spatial and social variations in car usage but here it is used to determine the probability of a vehicle being scrapped and also the initial age profile of all vehicles in the UK. Due to the lack of vehicle import/export between the UK and other countries it is possible to deal with the UK vehicle fleet as an isolated vehicle population.

It is further possible to split the vehicle population by fuel-type (diesel, petrol, electric).

$$V_f^{y+1} = \alpha P_f^{y+1} + \sum_a V_{a,f}^y (1 - \beta S_{a,f}) \quad (4)$$

Here f represents the fuel type with the following constraint.

$$\sum_{f=fueltype} V_f^y = \sum_{f=fueltype} \sum_{a=age} V_{a,f}^y \quad (5)$$

Finally, it is possible to calculate the total on-road emissions via:

$$Em^y = \sum_{a,f} V_{a,f}^y M_{a,f}^y E_{a,f}^y \quad (6)$$

Where $M_{a,f}^y$ represents the total distance travelled for a vehicle of fuel type f , age a and in year y and $E_{a,f}^y$ represents the emission rating for a given vehicle of fuel type f , age a and in year y .

2.2. Calculating UK embedded CO₂ emissions for vehicle manufacturing

In addition to the on-road CO₂ emissions it is also necessary to calculate the embedded CO₂ from vehicle production. EVs are typically a more resource intensive vehicle at the original manufacture point, and ignoring the CO₂ emitted during their production will artificially inflate their environmental benefit over traditional vehicles.

The embedded CO₂ will be given by the number of new vehicles produced in any given year for each specific fuel type and can be calculated for each year as:

$$Emb^y = \sum_f V_{a=0,f}^y PC_f^y \quad (7)$$

In Eq. (7) PC_f^y is the CO₂ produced in the manufacture of a vehicle with fuel type f in year y . $V_{a=0,f}^y$ is the national number of vehicles of fuel type f , with age 0 in year y .

2.3. On-road CO₂ emissions from EVs and ICEs

If EVs are to be a possible solution for reducing CO₂ emissions from the transport sector, then it must be shown that EVs will deliver a net reduction of CO₂ emissions if they replace internal combustion engine (ICE) vehicles on a like for like basis.

In SwitchEV, a large scale EV deployment and assessment research project within the UK [37,38], the installation of loggers on 44 EVs allowed for the collection of real world data, which included driving behaviour and vehicle recharging events. From the time of each re-charge event it was possible to assign a gCO₂/kWh value to the energy being stored in an EV battery. This value is derived from the power mix used to generate the electricity at the time of charge. When on a journey, the energy used by the vehicle is monitored so an average gCO₂/km travelled could be assigned to a particular trip.

Fig. 2 shows the average gCO₂/km for all trips. The average for the whole logged EV fleet during the period 2011–2013 was 85 g CO₂/km. This number was originally calculated using the 2011–2013 carbon intensity but assuming the same trip/charging patterns it can be shown that under the 2017 carbon intensity the average gCO₂/km would drop to 43 gCO₂/km. In the UK in 2010 the new car average was 140 gCO₂/km and in 2015 the Society of Motor Manufacturers and Traders (SMMT) has reported that this is now down to 121 gCO₂/km. The published figures from the SMMT were originally calculated based on

Fig. 2. Distribution of the CO₂/km for 63,000 EV journeys plus the average efficiency under 2011–2013 and 2017 carbon intensity. Also shown, the comparative values for an average new car in 2015.

the assumption that the stated fleet efficiencies are correct when in reality they are likely to be underestimated by 30–40 % [39]. Currently the targets are based on the stated fleet efficiencies, rather than actual CO₂ emissions. Therefore, if calculations going forward are based on the actual CO₂ emissions, then the ability of the fleet to hit the intended targets will be substantially impeded.

2.4. Embedded CO₂ emissions from vehicle manufacture

The full CO₂ emissions associated with an EV will also include the CO₂ produced during its manufacture as well as those produced during the car's lifetime. For the UK, the most comprehensive report on production-related CO₂ emissions from the manufacture of EVs and ICEs was published by Ricardo [40]. The report found that production in the UK of a standard mid-sized ICE will result in emissions of 5.6 tCO₂, whilst production of an equivalent sized EV will result in CO₂ emissions of 8.8 tCO₂.

The exact amount of CO₂ emissions from production of both ICEs and EVs is a matter of some dispute with a wide range of possible figures depending both on the assessment methodology used (e.g. “bottom up” versus “top down”) and the assumptions made in the production stage [41,42]. However, the most extensive work on battery production [43] provides a value of 150–200 kgCO₂/kWh. This leads to an excess of 4.2 tCO₂ for a 24 kWh battery (the battery size for the initial Nissan Leaf models which would correspond to an 80–100 km range) which, assuming the same CO₂ production emissions for the vehicle body and reduced production emissions for the EV drive train, will lead to a value similar to that shown in the earlier work by Ricardo. Hence, to more easily maintain compatibility with previous publications, the Ricardo production related CO₂ emissions will be used in this work.

The production-related CO₂ emissions are a product of the processes used to create the vehicle. Approximately 50% of the total energy used in the production of vehicles coming from the electricity grid [44] and as such this value will vary depending on the country of origin, and the expected year of manufacture. A vehicle constructed in a country which extensively uses coal-fired power stations will be more CO₂ intensive than the same vehicle constructed in a country dominated by renewable energy sources. For example, the CO₂ emissions from production of a vehicle produced in Japan would be higher than that same vehicle produced in the UK, due to the higher CO₂ intensity in Japan.

Similarly, a vehicle constructed in 2040 will be less CO₂ intensive (assuming a decarbonisation of the electricity production) than a vehicle constructed now. The UK has already observed strong grid decarbonisation with a reduction in 2017 of approximately 50% over 2010 levels [45]. This level of decarbonisation is higher than that originally estimated by the committee on Climate Change [12] but progress on decarbonisation beyond 2030 is uncertain. Beyond 2030 the carbon intensity projections split into two broad categories, with increased nuclear generation capability leading to a decarbonisation level of 80%

and no new nuclear generation giving a decarbonisation of 30–50% [45]. Within this work the decarbonisation is assumed to be either 80%, the UK government's expected level, or 50%, a more conservative “worst case” scenario.

The two most popular full electric vehicles in the UK (discounting plug-in hybrids such as the Mitsubishi Outlander PHEV) are the Nissan Leaf and the BMW i3, which are manufactured in the UK and Germany respectively. However the Nissan Leaf is substantially the most popular, with sales of over 19,000 to up to the end of 2017 compared to 9000 for the BMW i3 [46]. For the purposes of this work, it is therefore assumed that vehicles are manufactured in the UK as this is the main manufacturing location of the Nissan Leaf. While Tesla models belong to the best-selling EV models worldwide, they are not the best-selling model in the UK. In addition, due to their positioning as a high end vehicle, they are not indicative of the typical mass-market ICE for EV swap.

3. Results

3.1. Projections and impacts for EV adoption scenarios on on-road CO₂ emissions

As a preliminary step we calculated the on-road CO₂ emissions under multiple different scenarios from 2014 to 2050. This is a fundamental first step as it both allows us to evaluate how the different scenarios would serve to meet the transport climate reduction targets set out in the Climate Change Act 2008 [5] and also form the basis of a combined on-road and embedded production CO₂ emission value.

It was assumed that the current vehicle fleet would be steadily replaced with new vehicles, of which a certain proportion would be EVs. As the new vehicles are introduced, the CO₂ emissions of the entire fleet would reduce as the older, less efficient vehicles are replaced by either more modern, lower-emitting ICE vehicles or by EVs. Previous research [47] on Norwegian transport emissions has shown the effect of temporal lag on CO₂ emissions from vehicle transition rates.

It should be noted that the older vehicles are not necessarily being directly replaced by new vehicles. In reality first-hand vehicles would transition into second-hand vehicles, of which a proportion would be scrapped. However, the net result is that a certain number of new vehicles will be added to the fleet whilst a certain number of older vehicles will be scrapped. This transition is governed by Eq. (3). In addition, the stated gCO₂/km metric for each new ICE vehicle would improve with each year from 130 gCO₂/km in 2015 to the predicted pan-European target of 95 gCO₂/km in 2021 [48]. However, as has been previously shown [39] the type approval stated efficiencies, derived from laboratory tests, underestimate the CO₂ emissions when compared to on-road emissions tests and hence for the following calculations, the emissions have been increased to bring them in line with the more likely actual emissions. To account for this uncertainty in future ICE efficiency improvements, it is assumed that there are two scenarios for ICE vehicles representing a reduction to 60% and 80% of the 2011 values respectively.

In addition to ICE improvements in efficiency, there will be improvements in CO₂ emissions intensity of the power which is being used to recharge EVs. Finally, in addition to the turnover of vehicles, there will be a steady increase in the number of vehicles on the road according to the forecasts by the Department for Transport's National Transport Model [35].

The EV adoption levels are either “Business as Usual” or the targeted EV goals of no new ICE vehicles by 2040. The ICE vehicles are either a reduction in CO₂ emissions to 60% or 80% of current emissions levels. Similarly, the power grid decarbonisation is assumed to improve to either 50% or 80% over current rates with 80% being the expected decarbonisation and 50% a more conservative estimate. Each possibility for EV adoption rate, ICE efficiency improvement and power decarbonisation is combined and shown in table 1.

Fig. 3 presents the results of combining the different scenarios for

Table 1

Eight scenarios combining the options for EV adoption, ICE efficiency improvement and power supply decarbonisation.

Scenario	EV Adoption Rate	ICE CO ₂ Emission Intensity Reduction, 2014–2050	Power Supply Decarbonization Rate, 2014–2050
1	Business as Usual	60%	50%
2	Business as Usual	60%	80%
3	Business as Usual	80%	50%
4	Business as Usual	80%	80%
5	Targeted	60%	50%
6	Targeted	60%	80%
7	Targeted	80%	50%
8	Targeted	80%	80%

EV adoption, ICE efficiency improvements, and power supply decarbonisation.

Fig. 3 shows that the reduction in on-road CO₂ emissions falls into three broad groups:

Group 3, the targeted EV adoption scenario coupled with the 80% decarbonisation of the electricity supply, shows the largest reduction in on-road CO₂ emissions. Within this scenario, variation in ICE improvements has little effect on the total CO₂ reduction, in part due to the increased adoption of EVs and concomitant lack of ICE vehicles with the predicted efficiency improvements.

Group 2, the targeted EV adoption scenario coupled with the 50% decarbonisation of the electricity supply, shows the second largest reduction. In this scenario, similarly to group 3, the increased adoption of EVs means that increased ICE efficiencies have little overall impact but the lack of decarbonisation compared to group 3 leads to increased overall CO₂ emissions.

Finally, group 1 shows that with a greatly reduced level of EV uptake, it is the improvements in ICE efficiency that will deliver the greatest improvements in CO₂ emissions.

Fig. 3 also shows that there is minimal difference between any of the scenarios before 2030. Up to this point the reduction in CO₂ for the vehicle fleet is being driven by the turnover of ICE vehicles with older vehicles being replaced with newer, more efficient models.

3.2. Combined embedded production and On-Road CO₂ emissions

In addition to on-road CO₂ emissions, it is also necessary to look at the embedded CO₂ emissions from vehicle production.

In many life cycle assessments of EVs and ICEs, the effect of embedded CO₂ is ameliorated through applying the embedded CO₂ over the full life time of the vehicle. Whilst this is a valid approach in determining whether a vehicle is carbon neutral or not, it is not a valid approach when determining the overall CO₂ impact of a policy. The emitted CO₂ from production will be emitted over the course of a vehicle's manufacture, not over the course of its lifetime; hence the impact

of CO₂ will occur at the time of manufacture. The argument to include production CO₂ at the time of manufacture is even more striking from an analysis of the physical processes behind the CO₂ effect as a greenhouse gas, as the radiative forcing of CO₂ will have an impact from the time of emission [49].

In Fig. 4 we can see the impact of adding emitted CO₂ from vehicle production to the on-road CO₂ emissions. In addition, the effect of a decarbonisation of the electricity grid by 50% over 2014 levels is demonstrated. The decarbonisation [50] predicted for the UK will lead to a strong reduction in the embedded CO₂ associated with the manufacture of each vehicle. Non electricity dependent production processes are assumed, due to a lack of relevant studies, to follow the same trend.

In a similar fashion to the on-road CO₂, there is little difference between the two scenarios before 2030, in either the on-road CO₂ or the embedded CO₂. After 2030 the data begins to strongly diverge with the Targeted Scenario offering a reduction in total emitted CO₂ of approximately 20 MtCO₂ by 2050. In addition, the assumption of a 50% decarbonisation of the carbon intensity used in EV and ICE production, leads to a larger reduction in total emitted CO₂ by the passenger vehicle transport sector.

In Fig. 5 the relative proportions for the main transport emissions for the BAU and Targeted scenarios at 50% decarbonisation, as well as a third scenario with 80% decarbonisation. In each figure the CO₂ emissions are split into either embedded or on-road CO₂ and then further split by vehicle type, either ICE or EV.

For both the Targeted and Targeted plus 80% decarbonisation scenarios the largest single source of CO₂ emissions in 2050 come from the production of the vehicle. This is in contrast to the case currently where the vast majority of CO₂ is emitted from the on-road portion of the transport CO₂ emissions.

It can be seen that for the Targeted plus 80% decarbonisation scenario, the goal of 20% of 1990 CO₂ emission levels will be reached.

If production decarbonisation were not included in the three uptake scenarios then a much greater proportion of the CO₂ emissions for both the accelerated and targeted EV growth scenarios would be embedded

Fig. 3. Level of carbon reduction within the private vehicle sector for scenario variations.

Fig. 4. The change in total CO₂ emissions from production and on-road sources from 2014 to 2050, including embedded carbon, under two different decarbonisation and EV uptake scenarios.

in the productions of EVs. The impact of limited decarbonisation on embedded CO₂ would lead to overall CO₂ emissions at approximately 50% of the 2014 levels. This is substantially higher than is required by the Climate Change Act 2008.

4. Discussion

Across the world the question of how fast transport electrification can contribute to climate change mitigation targets is of high interest, given the challenge of steep decarbonisation required to keep global warming below 1.5 °C or 2 °C [51]. Our analysis shows that under all possible adoption scenarios, increased EV adoption will only show a significant benefit compared to the BAU case after 2030 and it will only lead to a change that is greater than 10% after 2040 (Fig. 5). Prior to this, the improvement in transport CO₂ emissions will be driven by the natural transition to a newer vehicle fleet, with the efficiency improvements this entails. Past 2040, it is only the 100% EV sales by 2040 ambition that will achieve the necessary reduction in on-road CO₂ emissions as stipulated in the 2008 Climate Change Act. Without the 2040 ambition it is predicted that the total on-road CO₂ emissions in

2050 will be 32 MtCO₂. This is substantially short of the required reduction to 18 MtCO₂ corresponding to 20% of 1990 emission levels.

However, this assumes that the on-road CO₂ emissions are the only metric which is applicable. The Climate Change Act does not specify which sectors must provide the necessary reduction in CO₂ only that the overall CO₂ level must be reduced by 80% on 1990 levels. Therefore it would be disingenuous to base the CO₂ emissions reduction calculations on only the on-road CO₂. Fig. 5 shows the result of including both ICE and EV embedded CO₂ emissions in the manufacture of vehicle. It can be seen that in both the Targeted and Targeted plus 80% decarbonisation scenario, the largest source of CO₂ emissions comes from the production of EVs. The on-road carbon footprint of the ICE vehicles is substantially reduced due to the turnover of vehicles past the 2040 target coupled with the improvements in efficiency for the new ICE vehicles, with the embedded production CO₂ of ICE reduced to zero due to the same target. On-road CO₂ for the EVs is also much smaller because of the decarbonisation of the electricity supply. If embedded CO₂ is included in the reduction calculations (and also included in the 1990 carbon target) then only the targeted plus 80% decarbonisation scenario will meet the 2050 targets, with a final total CO₂ emission of 16.5

Fig. 5. Total transport carbon from all sources for three scenarios, BAU, Targeted and Targeted with 80% decarbonisation. The dashed line represents the CO₂ target, set at 20% of 1990 levels.

MtCO₂. The targeted plus 50% decarbonisation scenario will show a final total emission of ~40 MtCO₂ (approximately 35% of 1990 levels) with the BAU Scenario substantially higher than that. This remains over 15 MtCO₂ more than the 20% of 1990 levels required.

From Fig. 5 it can be seen that the vast majority of CO₂ emissions reduction in the transport sector would be delivered simply by the replacement of old ICE vehicles with new, more efficient vehicles. It was shown that whilst improved efficiency in new build ICE vehicles coupled with the year on year turnover of vehicles is the largest driver in near term CO₂ reduction, it will not provide the needed mid to long term results. Achieving a lasting long term reduction in CO₂ emissions will be dependent on a greatly increased EV uptake coupled with an intensive decarbonisation of the power supply used in both the refuelling of EVs and also their production. Assuming that the current technological trends in CO₂ reduction for ICE/EV vehicles and their production will continue is not an unreasonable assumption, but it is also a wager on future technological improvements which could lead to a transport policy based on vehicle and production efficiencies which never arrive. For such transitions it is vital to understand not only the environmental effects of a move to EVs, but also how this will affect the costs, revenues, and business structures for EVs throughout their value and life cycle chain.

It should be stressed that the conclusions reached in this paper are dependent on a large series of assumptions on, for example, future vehicle numbers, vehicle scrappage rates, future improvements in vehicle efficiency and decarbonisation of the electric grid. Where possible these assumptions have been justified with reference to literature or statistics but a certain level of judgment has been used in balancing across scenarios. The numbers presented are also drawn from the UK case, they would not be representative of France, for example, where the CO₂ intensity of the electricity supply is significantly lower.

A final consideration is the issue of global and local air pollution. For a number of years now, it has been known that the Euro standard emissions for both petrol and diesel vehicles have resulted in some vehicle types emitting much more pollutants and CO₂ in real-world driving than is expected from the actual limits specified for the tests. This may, in some way, trigger policies that aim to reduce vehicle emissions for health purposes as well as reducing CO₂ [52]. Moreover, if conformance to the emissions in tests and those in real-world driving move closer to 1:1 following the next round of negotiations for post Euro 6 emissions regulations from 2021, it may provide a better defined pathway for motor manufacturers to offer more EV models and at a more affordable price. Coupled with this is the trend for cities to look towards introducing clean air zones where older, polluting vehicles will be financially penalised for being in these zones.

5. Conclusions

Our analysis shows that whilst EVs, coupled with a decarbonised power grid, are the best option for achieving long-term wide ranging decarbonisation of the transport system, they will show little impact in the short term. The effects of accelerated EV adoption will only become significantly apparent post 2030 as the older, less efficient ICE vehicles are aged out and this is not only based on the relatively slow diffusion of new vehicles into the vehicle fleet but, more relevantly, in up-front CO₂ emissions from vehicle production when the electricity sector has not yet been fully decarbonized. However, mitigation effects from on-road usage will become significant after 2030 as both CO₂ emissions from on-road usage and from vehicle production decrease further. A key-point to take away from this work is that there exists a natural lag between the implementation of any policy to drive EV adoption and its subsequent effect on CO₂ emissions on the transport fleet. Policies should be implemented with the understanding that they may not produce meaningful results for potentially a decade or more. Hence, to achieve mid-term climate targets, it is important to invest now in the electrification of passenger fleets, e.g. by public procurement, efficiency

standards, improved information provision [53], purchase taxes on non-electric vehicles, and charging infrastructures.

Whilst EVs will not provide a solution for near-term CO₂ mitigation, it will be possible to achieve the short term CO₂ emission reduction goals through demand-side solutions, rather than simply focussing on the supply side solutions implied by EVs. Whilst the majority of change in on-road CO₂ emissions (for light duty passenger vehicles especially) has come from technological improvements, demand side solutions to either reduce travel demand or induce a modal shift hold promise, often also for quality of life [54]. Demand side solutions of this nature can be implemented alongside the technological solutions and will provide a multiplier effect that will not be dependent on possible future technologies.

Acknowledgements

The researchers gratefully acknowledge the on-going support of the UK's Engineering and Physical Sciences Research Council (EPSRC) through the following funding awards: LC TRANSFORMS (Low Carbon Transitions of Fleet Operations in Metropolitan Sites EP/N010612/1); iBUILD (Infrastructure Business models, valuation and Innovation for Local Delivery EP/K012398/1) ReLiB (Recycling of Li-Ion Batteries) The Faraday Institution (FIRG005) and CESI (Centre for Energy Systems Integration EP/P001173/1).

References

- [1] Kahn Ribeiro S, Figueroa MJ, Creutzig F, Dubeux C, Hupe J, Kobayashi S. Chapter 9 - Energy End-Use: Transport. *Global Energy Assessment - Toward a Sustainable Future*. Cambridge University Press, Cambridge, UK and New York, NY, USA and the International Institute for Applied Systems Analysis, Laxenburg, Austria; 2012. pp. 575–648.
- [2] Creutzig F. Evolving narratives of low-carbon futures in transportation. *Transp Rev* Routledge 2016;36:341–60.
- [3] Heidrich O, Reckien D, Olazabal M, Foley A, Salvia M, de Gregorio Hurtado S, et al. National climate policies across Europe and their impacts on cities strategies. *J Environ Manage* 2016;168:36–45.
- [4] Heidrich O, Hill GA, Neameh M, Huebner Y, Blythe PT, Dawson RJ. How do cities support electric vehicles and what difference does it make? *Technol Forecast Soc Change* 2017;123:17–23.
- [5] Government HM. Climate Change Act 2008 [Internet]. 2008. Available: <https://www.legislation.gov.uk/ukpga/2008/27/contents>.
- [6] Committee on Climate Change. Progress report 2016: meeting carbon budgets. CCC; 2016.
- [7] Capros P, De Vita A, Tasios N, Siskos P, Kannavou M, Petropoulos A, et al. energy, transport and GHG emissions - trends to 2050. *Eur Community* 2016;2016:27. <https://doi.org/10.2833/9127>.
- [8] DfT. Greenhouse gas emissions by transport mode: United Kingdom, 2003-2016, [Internet]. Table ENV0201. 2016 Available: <https://www.gov.uk/government/statistical-data-sets/env02-greenhouse-gas-emissions>.
- [9] BEIS. Clean Growth Strategy [Internet]. 2017. Available: <https://www.gov.uk/government/publications/clean-growth-strategy>.
- [10] Office for Low Emission Vehicles. The Road to Zero. Department of Transport (DfT); 2018 Jul.
- [11] DfT. Ultra-low emission vehicles (ULEVs) registered for the first time (VEH0170) [Internet]. 2018. Available: https://www.gov.uk/government/uploads/system/uploads/attachment_data/file/715998/veh0170.ods.
- [12] Committee on Climate Change. Progress in preparing for climate change. Committee on Climate Change; 2015 Jun.
- [13] Hofmann J, Guan D, Chalvatzis K, Huo H. Assessment of electrical vehicles as a successful driver for reducing CO₂ emissions in China. *Appl Energy* 2016;184:995–1003.
- [14] Orsi F, Muratori M, Rocco M, Colombo E, Rizzoni G. A multi-dimensional well-to-wheels analysis of passenger vehicles in different regions: primary energy consumption, CO₂ emissions, and economic cost. *Appl Energy* 2016;169:197–209.
- [15] Alam MS, Hyde B, Duffy P, McNabola A. Assessment of pathways to reduce CO₂ emissions from passenger car fleets: Case study in Ireland. *Appl Energy* 2017;189:283–300.
- [16] Harvey LDD. Resource implications of alternative strategies for achieving zero greenhouse gas emissions from light-duty vehicles by 2060. *Appl Energy* 2018;212:663–79.
- [17] Vikström H, Davidsson S, Höök M. Lithium availability and future production outlooks. *Appl Energy* 2013;110:252–66.
- [18] eurostat. Energy, transport and environment indicators. eurostat; 2017 Nov.
- [19] Schäfer A. Structural change in energy use. *Energy Policy* 2005;33:429–37.
- [20] Nanaki EA, Koroneos CJ. Climate change mitigation and deployment of electric vehicles in urban areas. *Renewable Energy* 2016;99:1153–60.

- [21] Schipper L. Automobile use, fuel economy and CO₂ emissions in industrialized countries: Encouraging trends through 2008? *Transp Policy* 2011;18:358–72.
- [22] European Commission. Regulation Of The European Parliament And Of The Council setting emission performance standards for new passenger cars and for new light commercial vehicles as part of the Union's integrated approach to reduce CO₂ emissions from light-duty vehicles and amending Regulation (EC) No 715/2007 [Internet]. 2017. Available: <http://eur-lex.europa.eu/legal-content/EN/ALL/?uri=CELEX:52017PC0676&qid=1518371681956>.
- [23] Reckien D, Flacke J, Olazabal M, Heidrich O. The Influence of drivers and barriers on urban adaptation and mitigation plans-an empirical analysis of European cities. *PLoS ONE* 2015;10:e0135597.
- [24] DECISION No 406/2009/EC OF The European Parliament And Of The Council of 23 April 2009 on the effort of Member States to reduce their greenhouse gas emissions to meet the Community's greenhouse gas emission reduction commitments up to 2020. *Official Journal of the European Union*. 2009;L140: 136–148.
- [25] Sharma Ashish, Strezov Vladimir. Life cycle environmental and economic impact assessment of alternative transport fuels and power-train technologies. *Energy* 2017;133:1132–41.
- [26] Papson A, Creutzig F, Schipper L. Compressed Air Vehicles: Drive-Cycle Analysis of Vehicle Performance, Environmental Impacts, and Economic Costs. *Transp Res Rec*. SAGE Publications Inc; 2010;2191: 67–74.
- [27] Penna CCR, Geels FW. Climate change and the slow reorientation of the American car industry (1979–2012): An application and extension of the Dialectic Issue LifeCycle (DILC) model. *Res Policy* 2015;44:1029–48.
- [28] Hardman Scott. Understanding the impact of reoccurring and non-financial incentives on plug-in electric vehicle adoption – a review. *Transp Res Part A: Policy Practice* 2019;119:1–14.
- [29] Department of Energy and Climate Change (DECC). The carbon plan: Delivering our low carbon future. HM Government; 2011 Dec.
- [30] Department for Transport (DfT). Local Sustainable Transport Fund annual report 2011 to 2012. 2013 Jun.
- [31] Committee on Climate Change. Sectoral Scenarios for the Fifth Carbon Budget [Internet]. CCC; 2015 Nov. Available: <https://www.theccc.org.uk/publication/sectoral-scenarios-for-the-fifth-carbon-budget-technical-report/>.
- [32] DEFRA, DfT. Air quality plan for nitrogen dioxide (NO₂) in UK (2017) [Internet]. 2017. Available: <https://www.gov.uk/government/publications/air-quality-plan-for-nitrogen-dioxide-no2-in-uk-2017>.
- [33] Serradilla J, Wardle J, Blythe P, Gibbon J. An evidence-based approach for investment in rapid-charging infrastructure. *Energy Policy* 2017;106:514–24.
- [34] DfT. Road Traffic Forecasts 215. DfT; 2015.
- [35] Department for Transport (DfT). Anonymised MOT tests and results [Internet]. 2017. Available: <https://data.gov.uk/dataset/e3939ef8-30c7-4ca8-9c7c-ad9475cc9b2f/anonymised-mot-tests-and-results>.
- [36] Chatterton T, Barnes J, Wilson RE, Anable J, Cairns S. Use of a novel dataset to explore spatial and social variations in car type, size, usage and emissions. *Transp Res Part D: Trans Environ* 2015;39:151–64.
- [37] Blythe PP, Hill DG, Huebner DY, Suresh V, Austin J, Gray L, et al. North East England electric vehicle and infrastructure trials. *World Electric Vehicle J. Multidiscipl Digital Publishing Institute* 2012;5:856–65.
- [38] Robinson AP, Blythe PT, Bell MC, Hübner Y, Hill GA. Analysis of electric vehicle driver recharging demand profiles and subsequent impacts on the carbon content of electric vehicle trips. *Energy Policy* 2013;61:337–48.
- [39] ICCT. On-road testing of CO₂ and exhaust emissions from Euro 6 passenger cars in the EU: Technical Report [Internet]. 2016. Available: https://www.theicct.org/sites/default/files/publications/Euro%206%20on-road%20testing_ICCT_technical%20report_20160929.pdf.
- [40] Ricardo. Preparing for a Life cycle CO₂ Measure. LowCVP; 2011.
- [41] Miotti M, Supran GJ, Kim EJ, Trancik JE. Personal vehicles evaluated against climate change mitigation targets. *Environ Sci Technol. American Chemical Society* 2016;50:10795–804.
- [42] Hawkins TR, Singh B, Majeau-Bettez G, Strømman AH. Comparative environmental life cycle assessment of conventional and electric vehicles. *J Ind Ecol* 2013;17:53–64.
- [43] Romare M, Lisbeth D. The life cycle energy consumption and greenhouse gas emissions from lithium-ion batteries. IVL Swedish Environmental Research Institute 2017.
- [44] Sullivan, J L, Burnham, A, Wang, M, and Energy Systems. Energy-consumption and carbon-emission analysis of vehicle and component manufacturing.. United States: N. p., 2010. Web. doi:10.2172/993394.
- [45] Committee on Climate Change. Reducing UK emissions. 2018 Progress Report to Parliament. Committee on Climate Change; 2018 Jun.
- [46] Department for Transport (DfT). Licensed vehicles by make and model: Great Britain and United Kingdom [Internet]. 2018. Available: https://www.gov.uk/government/uploads/system/uploads/attachment_data/file/715986/veh0120.ods.
- [47] Fridstrøm L. From innovation to penetration: Calculating the energy transition time lag for motor vehicles. *Energy Policy*. 2017;108:487–502.
- [48] SMMT. NEW CAR CO₂ REPORT 2017. SMMT; 2017.
- [49] Forster P, Ramaswamy V, Artaxo P, Bernsten T, Betts R, Fahey DW, et al. Changes in atmospheric constituents and in radiative forcing. Chapter 2. *Climate Change 2007 The Physical Science Basis*. 2007.
- [50] BEIS. Digest of UK Energy Statistics 2017. Department for Business, Energy & Industrial Strategy; 2017.
- [51] IPCC, 2014: Climate Change 2014: Synthesis Report. Contribution of Working Groups I, II and III to the Fifth Assessment Report of the Intergovernmental Panel on Climate Change [Core Writing Team, R.K. Pachauri and L.A. Meyer (eds.)]. IPCC, Geneva, Switzerland, 151 pp.
- [52] Giardullo P, Sergi V, Carton W, Kenis A, Kesteloot C, Kazepov Y, et al. Air quality from a social perspective in four European metropolitan areas: research hypothesis and evidence from the SEFIRA project. *Environ Sci Policy*. 2016;65:58–64.
- [53] Neaimeh M, Hill GA, Hübner Y, Blythe PT. Routing systems to extend the driving range of electric vehicles. *IET Intel Transport Syst* 2013;7:327–36.
- [54] Creutzig F, Fernandez B, Haberl H, Khosla R, Mulugetta Y, Seto KC. Beyond technology: demand-side solutions for climate change mitigation. *Annu Rev Environ Resour. Annual Reviews* 2016;41:173–98.